

## PRODUCT DATE SHEET

## ATF DVI RED

### DESCRIPTION:

ARIOIL ATF DVI RED synthetic automatic gear oil based on chosen basic oils and additives for use in modern automatic transmissions, namely those used in GM Group vehicles.

Because it is fully downward compatible, this product complies with the most recent DEXRON-VI specification and fulfils the criteria of DEXRON-II and DEXRON-III.

### PLACE OF USE:

ARIOIL ATF DVI RED is recommended for the lubrication of:

- For General Motors automatic transmissions according to DEXRON VI and earlier specifications (DEXRON III and II).
- NOT suitable for CVT- Continuously Variable Transmissions and DCT - Dual Clutch Transmissions

### BENEFITS:

- Longer oil change intervals.
- Enhances both modern and old GM automatic gearboxes efficiency.
- Superior thermal stability and oxidation prevent the production of sludge and residue.
- Better cold start and fuel savings.
- Optimal performance and smooth changeover during the vehicle's service life

### BENEFITS:

ARIOIL ATF DVI RED Oils meet the requirements of:

- GM DEXRON VI
- GM DEXRON III
- GM DEXRON IID
- MERCON® LV

properties	Unit	Test Method	Values
Color		ASTM D 1500	6.0 – 8.0 (Red)
Density@15°C	g/ml	ASTM D 4052	0.874
Kin. viscosity@40°C	mm <sup>2</sup> /s	ASTM D 445	30.50
Kin. viscosity@100°C	mm <sup>2</sup> /s	ASTM D 445	6.0
viscosity Index		ASTM D 2270	147
Dynamic Viscosity @-20°C @-30°C @-40°C	mPa*s	ASTM D 2983	Max. 1,500 Max. 5,000 Max. 15,000
flash point(COC)	°C	ASTM D 92	214
Pour point	°C	ASTM D 97	-45

- These characteristics are typical of current production. While future production will conform to ARIOL specifications, these characteristics may vary.
- For further guidance on product health and safety, refer to the appropriate ARIOL Product Safety Data Sheet.
- Dispose of the used oil at an authorized collection point. Do not discharge into drains, soil, or water.