

PRODUCT DATA SHEET

TUKTUK 4T 20W/50

DESCRIPTION :

ARIOIL TUKTUK 20W-50 4T High-quality motorcycle oil for use all year round in four-stroke engines. The mixture of mineral base oils with advanced additives provides clear protection against wear and high resistance to thermal stress.

PLACE OF USE:

ARIOIL TUKTUK 20W-50 4T can be used in most modern four-stroke road & sports bikes, 4-stroke scooters, and tuk-tuks with or without integrated gearboxes and wet or dry clutches.

BENEFITS:

- High thermal stability.
- Prevents wear and saves fuel.
- It keeps the engine clean by preventing deposit formation.

SPECIFICATIONS:

ARIOIL TUKTUK 20W-50 4T meets the requirements of:

- API SJ/CD.
- JASO MA.

properties	Unit	Test Method	Values
Density@15°C	g/ml	ASTM D 4052	0.882
Kin. viscosity@40°C	mm ² /s	ASTM D 445	160.7
Kin. viscosity@100°C	mm ² /s	ASTM D 445	18.62
viscosity Index	-	ASTM D 2270	131
Apparent Viscosity by CCS@-30°C	mPa*s	ASTM D 5293	Max. 9500
Flashpoint (COC)	°C	ASTM D 92	236
Pour point	°C	ASTM D 97	-27
TBN	mgKOH/g	ASTM D 2896	7.7
Sulphated Ash	%	ASTM D 874	0,94

- These characteristics are typical of current production. While future production will conform to ARIOL specifications, these characteristics may vary.
- For further guidance on product health and safety, refer to the appropriate ARIOL Product Safety Data Sheet.
- Dispose of the used oil at an authorized collection point. Do not discharge into drains, soil, or water.